



Capacity	Type	Length	Width	Height	Inlet	Outlet	Slab Botm/Top	Wall Location	Weight
1,000 Gal.	Reg/HD	8'-6"	4'-10"	5'-4"	4'-6"	4'-3"	4" / 5"	2" / 8"	9,000 lbs.
1,000 Gal.	H-20	8'-6"	4'-10"	5'-8"	4'-8"	4'-5"	6" / 6"	2" / 8"	10,000 lbs.
1,000 Gal.	Low Boy	10'-6"	6'-4"	4'-0"	3'-2"	2'-11"	4" / 5"	2" / 8"	10,400 lbs.

DESIGN NOTES:

- 1) Regular and Heavy Duty Tanks are suitable for installation in NON-Traffic areas up to burial depths of 3 feet and 5 feet respectively.
- 2) Concrete Mix Design is 4,000 (5,000 for H-20) PSI standard at 28 days, Type 3 Cement.
- 3) Reinforcing steel ASTM A615, Grade 60, placed to an engineered design for teh H-20 tanks.
- 4) Shiplap joint sealed with butyl sealant.
- 5) All covers provided with pencil rod handles or lift loops.
- 6) POLYLOK PIPE SEALS standard at all pipe penetrations.
- 7) 4" PVC Tee Baffles can be placed at any of the (3) Inlets and Outlets.
- 8) Optional Center Wall held in place with aluminum angle clips and sealed to the tank walls with Sika Flex 1A sealant.